



**FabricAir®**  
**Combi Eco 85** 

FabricAir® Combi Eco 85 is a low-permeability, flame-retardant, Oeko-Tex 100 certified fabric made from dope dyed yarn. It is a strong and durable fabric; machine washable and retains its dimensions after washing (max. 0,5% shrinkage). The color is deeply embedded within the yarn, making it more resistant to fading, washing and UV exposure. Only limited air is able to pass through the fabric, achieved without the aid of chemical coatings. The production of this fabric is more sustainable, because chemical consumption and oxygen demand, water and energy consumptions are lower.

This fabric is rated for cleanrooms and associated controlled environments: Cleanliness Class 3 (ISO 14644-1 Table 1).

It comes with a 10-year warranty and is supplied in 5 standard colors, with the option of printed custom colors and custom patterns.

FEATURES AVAILABLE	
Washable	Yes
Warranty, years	10
Extended warranty option	Yes
Low-permeable	Yes
Flame retardant	Yes

STANDARD COLORS AVAILABLE	
3000 White	
3001 Blue	
3003 Dark Gray	
3004 Black	
3006 Light Gray	

COLORS AND PATTERNS AVAILABLE	
Coloring by surface print	
Seamless pattern by surface print	
Artwork, print	Yes
Logos, print	Yes
Lettering, print	Yes

# DATA: FabricAir® Combi Eco 85

## PROPERTIES

Fabric type:	Polyester	Dope dyed yarns
Weight:	335 (±7%) g/m <sup>2</sup>	EN ISO 12127:1997
Thickness:	0,45 mm	EN ISO 5084:1996
Permeability:	8 (±5%) m <sup>3</sup> /m <sup>2</sup> /h at 120 Pa	EN ISO 9237:1995
Strength - Warp:	2700 N	EN ISO 13934-1
Strength - Weft:	1600 N	EN ISO 13934-1
Shrinkage:	0,5% Max.	EN ISO 5077
Heat resistance - continuous:	from -40°C to +140°C	
Heat resistance - softening:	+240°C	

## CODE COMPLIANCE

Reaction to fire (European Union):	B-s1,d0	EN 13501-1
Reaction to fire (Denmark):	Yes	DS 428
Reaction to fire (France):	M1	NFP 92:507
Reaction to fire (USA):	Yes	UL 723
Reaction to fire (Canada):	Yes	ULC s102.2
Cleanrooms and associated controlled environments:	Class 3	EN ISO 14644-1

## PERFORMANCE CERTIFICATES

Safety Air Dispersion Systems:	Yes	UL 2518
--------------------------------	-----	---------

## ADDITIONAL APPROVALS

OEKO-TEX®:	Yes	OEKO-TEX® Standard 100
------------	-----	------------------------

## OPTIONAL FABRICAIR INNOVATIONS

All-in-One:	Yes
360° hoops:	Yes

## Disclaimer

FabricAir® believes that all data, statements, technical information, etc., listed in this Technical Data Sheet regarding the product and the use of the product are accurate and reliable. However, the product will only be covered by FabricAir®'s guarantees or warranty if the final use for the product has been approved by FabricAir® in writing. No representative is authorized to approve the final use of the product on behalf of FabricAir®.