

# FabricAir® Trevira

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
- Pre-rinse: 20°C (70°F) approx. 3 minutes without any detergent.
- Pre-wash: 40°C (104°F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
- Wash: 40°C (104°F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
- Rinse thoroughly after each washing.
- Do not add any softener.
- If possible, fix the ducts immediately after washing and spin-drying them. If ducts are made with All-in-One – reinsert the hoops after laundering.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Tumble at maximally 45°C (110°F) hot air.

## Storing the ducts

Make sure that the ducts are completely dry before folding them up. The ducts must be stored in a dry room.

# FabricAir® Combi 20

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
- Pre-rinse: 20°C (70°F) approx. 3 minutes without any detergent.
- Pre-wash: 40°C (104°F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
- Wash: 40°C (104°F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
- Rinse thoroughly after each washing.
- Do not add any softener.
- If possible, fix the ducts immediately after washing and spin-drying them. If ducts are made with All-in-One – reinsert the hoops after laundering.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Tumble at maximally 45°C (110°F) hot air.

## Storing the ducts

Make sure that the ducts are completely dry before folding them up. The ducts must be stored in a dry room.

# FabricAir® Combi 60

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
- Pre-rinse: 20°C (70°F) approx. 3 minutes without any detergent.
- Pre-wash: 40°C (104°F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
- Wash: 40°C (104°F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
- Rinse thoroughly after each washing.
- Do not add any softener.
- If possible, fix the ducts immediately after washing and spin-drying them. If ducts are made with All-in-One – reinsert the hoops after laundering.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Tumble at maximally 45°C (110°F) hot air.

## Storing the ducts

Make sure that the ducts are completely dry before folding them up. The ducts must be stored in a dry room.

# FabricAir® Combi 70

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
- Pre-rinse: 20°C (70°F) approx. 3 minutes without any detergent.
- Pre-wash: 40°C (104°F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
- Wash: 40°C (104°F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
- Rinse thoroughly after each washing.
- Do not add any softener.
- If possible, fix the ducts immediately after washing and spin-drying them. If ducts are made with All-in-One – reinsert the hoops after laundering.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Tumble at maximally 45°C (110°F) hot air.

## Storing the ducts

Make sure that the ducts are completely dry before folding them up. The ducts must be stored in a dry room.

# FabricAir® Combi 80

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
- Pre-rinse: 20°C (70°F) approx. 3 minutes without any detergent.
- Pre-wash: 40°C (104°F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
- Wash: 40°C (104°F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
- Rinse thoroughly after each washing.
- Do not add any softener.
- If possible, fix the ducts immediately after washing and spin-drying them. If ducts are made with All-in-One – reinsert the hoops after laundering.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Tumble at maximally 45°C (110°F) hot air.

## Storing the ducts

Make sure that the ducts are completely dry before folding them up. The ducts must be stored in a dry room.

# FabricAir® Combi 30

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
  - Pre-rinse: 20°C (70° F) approx. 3 minutes without any detergent.
  - Pre-wash: 40°C (104° F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
  - Wash: 40°C (104° F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
  - Rinse thoroughly after each washing.
  - Do not add any softener.
  - If possible, fix the ducts immediately after washing and spin-drying them.
- If ducts are made with All-in-One – reinsert the hoops after laundering.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Do NOT tumble!

## Storing the ducts

Make sure that the ducts are completely dry before folding them up.  
The ducts must be stored in a dry room.



# FabricAir® Combi 65

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
  - Pre-rinse: 20°C (70° F) approx. 3 minutes without any detergent.
  - Pre-wash: 40°C (104° F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
  - Wash: 40°C (104° F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
  - Rinse thoroughly after each washing.
  - Do not add any softener.
  - If possible, fix the ducts immediately after washing and spin-drying them.
- If ducts are made with All-in-One – reinsert the hoops after laundering.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Do NOT tumble!

## Storing the ducts

Make sure that the ducts are completely dry before folding them up. The ducts must be stored in a dry room.

# FabricAir® Combi 85

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
  - Pre-rinse: 20°C (70° F) approx. 3 minutes without any detergent.
  - Pre-wash: 40°C (104° F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
  - Wash: 40°C (104° F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
  - Rinse thoroughly after each washing.
  - Do not add any softener.
  - If possible, fix the ducts immediately after washing and spin-drying them.
- If ducts are made with All-in-One – reinsert the hoops after laundering.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Do NOT tumble!

## Storing the ducts

Make sure that the ducts are completely dry before folding them up.  
The ducts must be stored in a dry room.



# FabricAir® Combi 90

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
  - Pre-rinse: 20°C (70° F) approx. 3 minutes without any detergent.
  - Pre-wash: 40°C (104° F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
  - Wash: 40°C (104° F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
  - Rinse thoroughly after each washing.
  - Do not add any softener.
  - If possible, fix the ducts immediately after washing and spin-drying them.
- If ducts are made with All-in-One – reinsert the hoops after laundering.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Do NOT tumble!

## Storing the ducts

Make sure that the ducts are completely dry before folding them up. The ducts must be stored in a dry room.

# FabricAir® Lite 5

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
- Pre-rinse: 20°C (70° F) approx. 3 minutes without any detergent.
- Pre-wash: 40°C (104° F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
- Wash: 40°C (104° F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
- Rinse thoroughly after each washing.
- Do not add any softener.
- If possible, fix the ducts immediately after washing and spin-drying them.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Do NOT tumble!

## Storing the ducts

Make sure that the ducts are completely dry before folding them up.  
The ducts must be stored in a dry room.

# FabricAir® Lite 10

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
- Pre-rinse: 20°C (70° F) approx. 3 minutes without any detergent.
- Pre-wash: 40°C (104° F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
- Wash: 40°C (104° F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
- Rinse thoroughly after each washing.
- Do not add any softener.
- If possible, fix the ducts immediately after washing and spin-drying them.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Do NOT tumble!

## Storing the ducts

Make sure that the ducts are completely dry before folding them up.  
The ducts must be stored in a dry room.

# FabricAir® Lite 15

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
- Pre-rinse: 20°C (70° F) approx. 3 minutes without any detergent.
- Pre-wash: 40°C (104° F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
- Wash: 40°C (104° F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
- Rinse thoroughly after each washing.
- Do not add any softener.
- If possible, fix the ducts immediately after washing and spin-drying them.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Do NOT tumble!

## Storing the ducts

Make sure that the ducts are completely dry before folding them up.  
The ducts must be stored in a dry room.

# FabricAir® Lite 20

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



## Washing procedure

- Optimum result of laundering can be achieved by turning the ducts inside out before process. If ducts are made with All-in-One – remove the hoops before laundering.
- Pre-rinse: 20°C (70° F) approx. 3 minutes without any detergent.
- Pre-wash: 40°C (104° F) approx. 10 minutes. Quantities of detergent as recommended by the supplier.
- Wash: 40°C (104° F) approx. 20 minutes. Quantities of detergent as recommended by the supplier.
- Rinse thoroughly after each washing.
- Do not add any softener.
- If possible, fix the ducts immediately after washing and spin-drying them.
- Start the ventilation system in order to dry the ducts.



## Tumbling

Do NOT tumble!

## Storing the ducts

Make sure that the ducts are completely dry before folding them up.  
The ducts must be stored in a dry room.

# FabricAir® Glass

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



### Washing procedure

Do not wash by machine.



### Tumeling

Do NOT tumble!

## Storing the ducts

Make sure that the ducts are completely dry before folding them up. The ducts must be stored in a dry room.



# FabricAir® Poly

## General information

In order to ensure a long and optimum distribution of air, it is necessary to keep the ducts free from dirt and dust. An effective maintenance ensures that the ducts supply the required quantity of air and it also ensures an optimum life for the FabricAir® Dispersion System.



### Washing procedure

Do not wash by machine.



### Tumeling

Do NOT tumble!

## Storing the ducts

Make sure that the ducts are completely dry before folding them up. The ducts must be stored in a dry room.