



FabricAir® Combi 65

FabricAir® Combi 65 is a nonpermeable, Oeko-Tex 100 certified fabric.It is a strong and durable fabric; machine washable and retains its dimensions after washing (max. 0.5% shrinkage).

This fabric is rated for cleanrooms and associated controlled environments: Cleanliness Class 3 (ISO 14644-1 Table 1). It comes with a 10-year warranty and is supplied in 9 standard colors, with the option of printed custom colors and custom patterns.

Shape retention options, as well as all flow models, except FabFlowTM, are available and it is compatible with the FabricAir® VarioDuctTM.

FEATURES AVAILABLE		
Washable	Yes	
Warranty, years	10	
Non-permeable	Yes	

STANDARD COLORS AVAILABLE		
3000 White	3	
3001 Blue		
3002 Orange		
3003 Dark Gray		
3004 Black		
3005 Red		
3006 Light Gray		
3007 Green		
3008 Tan		

COLORS AND PATTERNS AVAILABLE		
Dye colors available	No	
Coloring by Surface Print	Yes	
Seamless Pattern by surface print	Yes	
Artwork, print	Yes	
Logos, print	Yes	
Lettering, print	Yes	

DATA: FabricAir® Combi 65

PROPERTIES

Fabric type:	Polyester	
Weight:	285 [8.50] g/m² [oz/yd²]	EN ISO 12127:1997 (ASTM D3776-96)
Thickness:	0,45 [0.018] mm [inch]	EN ISO 5084:1996 (ASTM D1777-96)
Permeability:	[[0 CFM/ft² at 0.5" inwg]	EN ISO 9237:1995 (ASTM D737, Frazier)
Strength - Warp:	2700 N	EN ISO 13934-1
Strength - Weft:	900 N	EN ISO 13934-1
Shrinkage:	0,5% Max.	EN ISO 5077
Heat resistance - continuous:	from -40°C [-40°F] to +140°C [+284°F]	
Heat resistance - softening:	+240°C [+464°F]	

CODE COMPLIANCE

Reaction to fire (Republic of China):	B-s1,d0,t1	GB 8624
Cleanrooms and associated controlled environments:	Class 3	EN ISO 14644-1

ADDITIONAL APPROVALS

OPTIONAL FABRICAIR INNOVATIONS

All-in-One:	Yes	
360° hoops:	Yes	

Disclaimer

FabricAir® believes that all data, statements, technical information, etc., listed in this Technical Data Sheet regarding the product and the use of the product are accurate and reliable. However, the product will only be covered by FabricAir®'s guarantees or warranty if the final use for the product has been approved by FabricAir® in writing. No representative is authorized to approve the final use of the product on behalf of FabricAir®.

