



FabricAir®
Combi Eco 60 

FabricAir® Combi Eco 60 is a permeable, self-extinguishing, Oeko-Tex 100 certified fabric made from dope dyed yarn. It is a strong and durable fabric; machine washable and retains its dimensions after washing (max. 0.5% shrinkage). The permeability is uniform (max. 5% variation) and achieved by thermo-fixation. The color is deeply embedded within the yarn, making it more resistant to fading, washing and UV exposure. The production of this fabric is more sustainable, because of lower chemical consumption and oxygen demand.

This fabric is rated for cleanrooms and associated controlled environments: Cleanliness Class 3 (ISO 14644-1 Table 1).

It comes with a 10-year warranty and is supplied in 5 standard colors, with the option of printed custom colors and custom patterns.

FEATURES AVAILABLE	
Washable	Yes
Warranty, years	10
Extended warranty option	Yes
Permeable	Yes

STANDARD COLORS AVAILABLE	
3000 White	
3001 Blue	
3003 Dark Gray	
3004 Black	
3006 Light Gray	

COLORS AND PATTERNS AVAILABLE	
Coloring by surface print	
Seamless pattern by surface print	
Artwork, print	Yes
Logos, print	Yes
Lettering, print	Yes

DATA: FabricAir® Combi Eco 60

PROPERTIES

Fabric type:	Polyester	Dope dyed yarns
Weight:	8.11 (±7%) oz/yd ² [275 (±7%) g/m ²]	EN ISO 12127:1997
Thickness:	0.018 inch [0,45 mm]	EN ISO 5084:1996
Permeability:	2 (±5%) CFM/ft ² at 0.5" inwg [40 (±5%) m ³ /m ² /h at 120 Pa]	EN ISO 9237:1995
Strength - Warp:	2700 N	EN ISO 13934-1
Strength - Weft:	900 N	EN ISO 13934-1
Shrinkage:	0.5% Max.	EN ISO 5077
Heat resistance - continuous:	from -40 to +284 °F [from -40 to +140 °C]	
Heat resistance - softening:	+464°F [+240°C]	

CODE COMPLIANCE

Reaction to fire (Canada):	Yes	ULC s102.2
Cleanrooms and associated controlled environments:	Class 3	EN ISO 14644-1

ADDITIONAL APPROVALS

OEKO-TEX®:	Yes	OEKO-TEX® Standard 100
------------	-----	------------------------

OPTIONAL FABRICAIR INNOVATIONS

All-in-One:	Yes
360° hoops:	Yes

Disclaimer

FabricAir® believes that all data, statements, technical information, etc., listed in this Technical Data Sheet regarding the product and the use of the product are accurate and reliable. However, the product will only be covered by FabricAir®'s guarantees or warranty if the final use for the product has been approved by FabricAir® in writing. No representative is authorized to approve the final use of the product on behalf of FabricAir®.